

**PROFESSIONAL
SANDING SYSTEMS**



Discs

RHYNOFIBRE C

Silver



| FEPA-P Grit | 16 | 20 | 24 | 30 | 36 | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 280 | 320 | 360 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 | 2000 | 2500 |
|-------------|---------------------------|----|----|----|----|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|
| Backing | Vulcanized Fibre 0,8 mm | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Abrasive | Silicon Carbide | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Bonding | Modified Synthetic Resins | | | | | | | | | | | | | | | | | | | | | | | | | | |

Application Suggestions

Grinding or finishing of non-ferrous materials.
Treatment of surfaces made of natural or synthetic stone, concrete, ceramics, glass, titanium and plastics.
Construction and decoration industry.

Features and Benefits

High mechanical resistance.
Very good stock removal.
Very high edge stability.
Very long life time.

